



Package is configured, corner-trimmed, and calibrated for 5,000 divisions before shipping

CHOICE OF 120 OR 120 PLUS



FLOOR SCALE APPROVALS



Measurement Canada Approved

INDICATOR APPROVALS



Measurement Canada Approved*



* 120 Plus - Approvals pending for Measurement Canada

SPECIFICATIONS

SUMMIT 3000 FLOOR SCALE

APPROVALS:

NTEP Certified, CC# 92-001A9;
Measurement Canada approved, AM-5530

END LOAD CAPACITY

100% full scale at 5000lb (2500kg)
80% full scale at 10,000lb (5000kg)

CABLE LENGTH:

20ft (6.1 m) (for connecting j-box to indicator)

WARRANTY:

Two-year limited warranty

FLOOR SCALE AND INDICATOR PACKAGE

Package includes DIGI® Summit® 3000 floor scale, 120 PLUS digital weight indicator with tilt stand, 20ft load cell cable with quick disconnect, configured and calibrated

STANDARD FEATURES

Summit™ 3000 Floor Scale

- Four NTEP Certified alloy steel shear beam load cells
- Top access junction box
- Rugged diamond safety treadplate steel deck
- Four adjustable rigid polyurethane rubber feet, 3in (76.2mm) diameter
- Signal trim summing board housed in ABS enclosure
- Threaded eyebolt hole (1/2–13NC) located in the center of the deck for easy lifting
- 20ft of EL147 load cell cable with quick disconnect
- Package configured and calibrated for 5,000 divisions

120 Digital Weight Indicator

- Large .8in (20.3mm) Light Emitting Diode (LED) display
- Five-button operation
- Full front panel digital calibration and configuration

120 PLUS Digital Weight Indicator

- Large .8in backlit Liquid Crystal Display (LCD)
- 115 or 230VAC wall adaptor with rechargeable battery

120/120 PLUS DIGITAL WEIGHT INDICATOR

POWER:

120/120 Plus:
Line voltages: 115 or 230 VAC
Frequency: 50 or 60 Hz

120 Plus: (estimated battery life)
60 hours with 1 x 350 Ω
40 hours with 4 x 350 Ω
Charge time 8 hours

OPERATING TEMPERATURE:

-10°C to 40°C/14°F to 104°F (legal)
-10°C to 50°C/14°F to 122°F (industrial)

RATING/MATERIAL:

Enclosure: heavy gauge ABS

120 APPROVALS:

NTEP Certified 6,000 Divisions, Class III/IIIL,
CC# 03-059; Measurement Canada approved, AM-5517,
Class III/IIILD at 6,000 Divisions; TC7072; T 5692 at 5,000 Divisions;
CE marked

120 PLUS APPROVALS:

NTEP Certified 6,000 Divisions, Class III/IIIL, CC# 03-059; Measurement Canada Pending, OIML approved, TC 7335; T7334 at 10,000 Divisions

WARRANTY:

1-year limited warranty

Floor Scale and Indicator Package

PART #	SIZE (W x L x H)	CAPACITY	EST. SHIP WEIGHT	PRICE
FLOOR SCALE AND INDICATOR PACKAGE (SINGLE SCALE)				
Package includes DIGI® Summit® 3000 floor scale, 120/120 PLUS digital weight indicator with tilt stand, 20ft load cell cable with quick disconnect, configured and calibrated				
115 VAC (120)				
78772.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	.315 lb	Consult
78773.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	.315 lb	Consult
115 VAC (120 PLUS)				
106913.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	.315 lb	Consult
106914.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	.315 lb	Consult
230 VAC (120)				
78780.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	.315 lb	Consult
78781.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	.315 lb	Consult
230 VAC (120 PLUS)				
106915.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	.315 lb	Consult
106916.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	.315 lb	Consult
115 VAC Canadian Weights and Measures (120)				
78776.....	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	.315 lb	Consult
78777.....	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	.315 lb	Consult
115 VAC Canadian Weights and Measures (120 PLUS)				
106917.....	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	.315 lb	Consult
106918.....	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	.315 lb	Consult

FLOOR SCALE AND INDICATOR PACKAGE (5-SCALE PACKAGE)

Packages include five DIGI® Summit® 3000 floor scales, five 120/120 PLUS digital weight indicators with tilt stands, five 20ft load cell cables with quick disconnect, configured and calibrated

115 VAC (120)				
78774.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
78775.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
115 VAC (120 PLUS)				
106929.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
106930.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
230 VAC (120)				
78782.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
78783.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
230 VAC (120 PLUS)				
106931.....	4 ft x 4 ft x 3.625 in	5,000 lb x 1 lb	1665 lb	Consult
106932.....	4 ft x 4 ft x 3.625 in	10,000 lb x 2 lb	1665 lb	Consult
115 VAC Canadian Weights and Measures (120)				
78778.....	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	1665 lb	Consult
78779.....	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	1665 lb	Consult
115 VAC Canadian Weights and Measures (120 PLUS)				
106933.....	4 ft x 4 ft x 3.625 in	2,500 kg x 0.5 kg	1665 lb	Consult
106934.....	4 ft x 4 ft x 3.625 in	5,000 kg x 1 kg	1665 lb	Consult

OPTIONS/ACCESSORIES

DIGI® Summit® 3000 Floor Scale

75819	Floor anchor plates, mild steel (set of two)	Consult
76012	Additional operating manual	Consult

120 Digital Weight Indicator

77925	Revolution® III Scale Software*	Consult
78611	Additional power supply, 115 VAC	Consult
76699	Additional operating manual	Consult

* Revolution® III can be downloaded for free from the distributor section of our Web site at www.ricelake.com

Access ramps, pit frames, bumper guards and portability frames available. See pages F-31 thru F-37